



IS = 14-18 dB

Trittschalldämmung (Lw)

Impact sound reduction / Isolation du bruit d'impact / Riduzione del rumore da calpestio



RWS = 38,1%

Ln, walk, A = 81,9 dB

Gehschallverbesserung

Reflected walking sound / Reduction du bruit de choc / Riduzione del riverbero da camminamento



ρ = 950 kg/m²

Dichte

Density / Densite / Densita



e = 1,5 mm

Dicke


Thickness / Épaisseur / Spessore



R = 0,0091 m²K/W

Wärmewiderstand

Thermal resistance / Résistance thermique / Resistenza termica



CS = >1677 kPa

Druckfestigkeit

Compressive strength / Résistance à la compression / Resistenza alla compressione

Diese Trittschallunterlage hat eine integrierte Dampfsperffolie und ist für Warmwasser und elektrischer Fussbodenheizung geeignet!



Montageanleitung

Installation Instructions Instructions d'installation istruzioni di installazione

Bitte beachten Sie auch die Anweisungen des Bodenbelag-Herstellers / Please also follow the flooring manufacturer's instructions / S.v.p. suivez aussi les instructions du fabricant du revêtement de sol / Seguire anachi le istruzioni del produttore del pavimento

Hergestellt für:
HWZ International AG, Untere
Gründlistrasse 23, 6055 Alpnach
Dorf, Switzerland, info@hwzi.ch.

